

# ANYCERT-CCC-RVV

## RVV 多芯软导体聚氯乙烯绝缘护套电缆



### 应用

- 适用于一般电子、电器设备电源连线。

### 结构

- 单根或多股退火裸铜丝或镀锡铜丝绞合
- PVC 绝缘
- PVC 护套

### 特点

- 可通过 GB18380.1 垂直耐燃试验
- 使用标准厚度、易剥、易裁
- 具有抗酸碱、防霉、耐油、防潮、环保等特性

### 性能

- 额定电压：300/500V
- 额定温度：70℃

页码

编号	芯数 x 截面 mm <sup>2</sup>	绝缘厚度 mm	护套厚度 mm	平均外径		70℃时绝缘电阻最小值 MΩ.km
				下限 mm	上限 mm	
1005RVV0020005	2 x 0.5	0.6	0.7	5.2	6.6	0.012
1005RVV00200075	2 x 0.75	0.6	0.8	5.7	7.2	0.012
1005RVV002001	2 x 1.0	0.6	0.8	5.9	7.5	0.010
1005RVV0020015	2 x 1.5	0.7	0.8	6.8	8.6	0.010
1005RVV0020025	2 x 2.5	0.8	0.9	8.2	10.3	0.012
1005RVV0030005	3 x 0.5	0.6	0.7	5.5	7	0.010
1005RVV00300075	3 x 0.75	0.6	0.8	6	7.6	0.010
1005RVV003001	3 x 1.0	0.6	0.8	6.3	8	0.011
1005RVV0030015	3 x 1.5	0.7	0.9	7.4	9.4	0.010
1005RVV0030025	3 x 2.5	0.8	1	9	11.2	0.010
1005RVV0040005	4 x 0.5	0.6	0.8	6.2	7.9	0.009
1005RVV00400075	4 x 0.75	0.6	0.8	6.6	8.3	0.007
1005RVV004001	4 x 1.0	0.6	0.8	6.9	8.7	0.006
1005RVV0040015	4 x 1.5	0.7	0.9	8.2	10.2	0.011
1005RVV0040025	4 x 2.5	0.8	1.1	10.1	12.5	0.010
1005RVV0050005	5 x 0.5	0.6	0.8	6.8	8.6	0.010
1005RVV00500075	5 x 0.75	0.6	0.9	7.4	9.3	0.009
1005RVV005001	5 x 1.0	0.6	0.9	7.8	9.8	0.007
1005RVV0050015	5 x 1.5	0.7	1	9.1	11.4	0.006
1005RVV0050025	5 x 2.5	0.8	1.1	11	13.7	0.011
1005RVV0050005	6 x 0.5	0.6	0.9	7.6	9.6	0.010
1005RVV00500075	6 x 0.75	0.6	0.9	8.1	10.1	0.010
1005RVV005001	6 x 1.0	0.6	1	8.7	10.8	0.009
1005RVV0050015	6 x 1.5	0.7	1.1	10.2	12.6	0.007
1005RVV0050025	6 x 2.5	0.8	1.2	12.2	15.1	0.006
1005RVV0070005	7 x 0.5	0.6	0.9	8.3	10.4	0.011